











WHMTS Pictograms Not Controlled

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: 700 Series Board, Serie 700 de Fiberglas

MSDS Manufacturer Number: 17020-NAM

Synonyms:

700 Series Board Unfaced, Serie 700 de Fiberglas, AF 220, AF 500 Series, AT-400 700 Series, Equipment & Appliance, Fabrication Board, Fiberglass Basic for Molding, FLEXWRAP®, Insul-Quick®, Jet-Cel Acoustical, Marine Hullboard, Muffler Packing, NuKon® insulation blanks, Pipe & Tank Insulation, Railroad, SCR Board, SelectSound® Sanded Acoustical Board, SR & HT Range, TIW Thermal Insulation

Wool, Transportation, Type 1000

Product Use/Restriction: Unfaced Insulation Board

Owens Corning Insulating Systems, LLC Manufacturer Name:

One Owens Corning Parkway Address:

Toledo, OH 43659

Customer Service Phone 1-800-GET-PINK or 1-800-438-7465

Number:

Health Issues Information: 1-800-GET-PINK or 1-800-438-7465 Technical Product 1-800-GET-PINK or 1-800-438-7465

Information:

Emergency Phone Number: 1-419-248-5330 (after 5pm ET and weekends)

CHEMTREC: 800-424-9300 (24 hours everyday).

Canutec: (613) 996-6666 (Canada 24 hours everyday).

Website: www.owenscorning.com MSDS Creation Date: December 16, 1997 MSDS Revision Date: August 01, 2013



SECTION 3: HAZARDS IDENTIFICATION

Applies to Product

Emergency Overview: Exposure to dust may be irritating to eyes, nose, and throat.

Route of Exposure: Eye contact Skin contact

Inhalation.

Potential Health Effects:

Eve: May cause slight irritation. Skin: May cause slight skin irritation.

Inhalation: May cause irritation of respiratory tract. Ingestion: Ingestion of this product is unlikely.

This product contains a component which is listed by IARC, OSHA or NTP. See Section 11 for additional Carcinogenicity:

Potential Environmental Effects: There is no known ecological information for this material.

Aggravation of Pre-Existing Conditions: Chronic respiratory or skin conditions may temporarily worsen from exposure to this product.

> Appearance and Odor: Pink, yellow, or tan fibrous material with faint resin odor.

> > would influence the classification of this product.

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent	EC Num.
Cured Binder	25104-55-6	5 - 20 by weight	
Fiber Glass (Wool)	65997-17-3	85 - 96 by weight	266-046-0
Non-Hazardous Statement:	The remaining components of th	is product are non-hazardous or are i	in a small enough quantity as to not

meet regulatory thresholds for disclosure. These components contain no substances or impurities which

700 Series Board, Serie 700 de Fiberglas Product Code: 17020-NAM Revision:: 08/01/2013

Page 1 of 5

SECTION 4: FIRST AID MEASURES

Eve Contact: Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of

the eyes by separating the eyelids with fingers.

Do not rub or scratch eyes.

If eye irritation persists, consult a specialist.

Skin Contact:

Wash off immediately with soap and cold water.

DO NOT use warm water because this will open up the pores of the skin, which will cause further penetration of the fibers.

Use a wash cloth to help remove fibers. DO NOT rub or scratch affected areas Remove contaminated clothing.

If irritation persists get medical attention.

Never use compressed air to remove fibers from the skin.

If fibers are seen penetrating from the skin, the fibers can be removed by applying and removing adhesive tape so that the fibers adhere to the tape and are pulled out of the skin.

Inhalation:

If symptoms persist, call a physician.

Inaestion: Accidental ingestion of this material is unlikely.

If this does occur, watch person for several days to make sure intestinal blockage does not occur. Rinse mouth with water and drink water to remove fibers from the throat.

If symptoms persist, call a physician.

Note to Physicians: Treat symptomatically.

SECTION 5: FIRE FIGHTING MEASURES

Flammable Properties: Non Flammable.

Flash Point:

Flash Point Method: Not applicable. Lower Flammable/Explosive Limit: Not applicable. Upper Flammable/Explosive Limit: Not applicable. Extinguishing Media: dry chemical

foam.

carbon dioxide (CO2).

Protective Equipment: Wear self-contained breathing apparatus (SCBA) and full fire fighting protective gear.

Carbon monoxide. Carbon dioxide. Hazardous Combustion Byproducts:

Ammonia.

Other undetermined compounds could be released in small quantities.

Universal Fire And Explosion

Hazards

Not available

NFPA Ratings:

NFPA Health: NFPA Flammability: 1 NFPA Reactivity: 0

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personnel Precautions: Avoid contact with skin and eyes.

Environmental Precautions: Prevent further leakage or spillage if safe to do so.

Spill Cleanup Measures: Pick or scoop up material and put into a suitable container for disposal as a non-hazardous waste.

* Use an industrial vacuum cleaner with a high efficiency filter to clean up dust and fiber contamination.

Methods for containment: This material will settle out of the air.

Prevent from spreading by covering, diking or other means.

Methods for cleanup: Use an industrial vacuum cleaner with a high efficiency filter to clean up dust and fiber contamination.

Avoid dry sweeping

Pick up and transfer to properly labeled containers.

SECTION 7: HANDLING and STORAGE

Handling Avoid dust formation.

Do not breathe dust

Wear personal protective equipment.

Storage: Keep product in its packaging until use to minimize potential dust generation.

Product should be kept dry and undercover.

Hygiene Practices: Wash hands before breaks and immediately after handling the product.

Remove and wash contaminated clothing before re-use.

700 Series Board, Serie 700 de Fiberglas Product Code: 17020-NAM Revision:: 08/01/2013

SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls: Provide local exhaust and/or general ventilation to maintain exposure below regulatory and

recommended limits.

Dust collection system must be used in transferring operations, cutting or machining or other dust generating processes, such as using power tools.

Vacuum or wet clean-up methods should be used.

Eye/Face Protection: Safety glasses with side-shields.

Skin Protection Description:

Protective gloves. Long sleeved shirt and long pants.

When workers are facing airborne particulate/dust concentrations above the exposure limit they must use appropriate certified respirators. Respiratory Protection:

A properly fitted NIOSH approved disposable N 95 type dust respirator or better is recommended.

When the temperature of the surface being insulated exceeds 250°F (121°C), including initial startup, the binder in these products may undergo various degrees of decomposition depending on the temperature in the application. Other Protective:

The need for respiratory protection will vary according to the airborne concentration of the decomposition products released and accumulated in the area.

Wear the appropriate respiratory protection according to the conditions and exposure levels in the area.

General Hygiene Considerations: Wash hands before breaks and immediately after handling the product.

Remove and wash contaminated clothing before re-use

EXPOSURE GUIDELINES

Ingredient	Guideline OSHA	Guideline NIOSH	Guideline ACGIH	Ontario Canada	Mexico
Formaldehyde	PEL: 0.75 ppm STEL: 2 ppm	REL-TWA: 0.016 ppm REL-Ceiling/Peak: 0.1 ppm	TLV-Ceiling/Peak: 0.3 ppm	TWAEV-CEV: 0.3 ppm	LMPE-Ceiling/Peak: 2 ppm
Fiber Glass (Wool)	PEL-TWA: 1 f/cc (Respirable)		TLV-TWA: 1 f/cc (Respirable)	TWAEV-TWA: 0.05 mg/m3 or 1 f/cc STEL: 0.6 mg/m3	TWA: 0.15 mg/m3

SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

Physical State: Solid. Physical State Appearance: Fibrous. Odor: organic. **Boiling Point:** No Data Melting Point: No Data Specific Gravity: No Data

Solubility: Insoluble. in water.

Vapor Density: No Data Vapor Pressure: No Data Evaporation Rate: No Data pH: No Data Viscosity: Not applicable. Flash Point:

Flash Point Method: Not applicable.

SECTION 10: STABILITY and REACTIVITY

Chemical Stability: Stable under normal conditions.

Hazardous Polymerization: Hazardous polymerization does not occur.

Conditions to Avoid: None expected

Incompatible Materials: No materials to be especially mentioned.

Special Decomposition Products: See Section 5 of MSDS for hazardous decomposition products during a fire.

SECTION 11: TOXICOLOGICAL INFORMATION

Applies to Product:

Acute Toxicity: Dusts may cause mechanical irritation to eyes and skin. Ingestion may cause transient irritation of

throat, stomach and gastrointestinal tract. Inhalation may cause coughing, nose and throat irritation, and sneezing. High exposures may cause difficulty breathing, congestion, and chest tightness.

Carcinogens:							
ACGIH NIOSH OSHA IARC NTP							MEXICO
Formaldehyde		NIOSH	OSHA:	Group 1 -	K - Known to be		A2 - Suspected
		carcinogen	Designated	Carcinogenic to	a human		Human

			carcinogen	humans.	carcinogen.	Carcinogen
Fiber Glass (Wool)	A3 Animal Carcinogen	No Data	No Data	Group 3 - Not Classifiable as to	Biosoluble glass wool is not	A3 Animal Carcinogen
				its Carcinogenicity to Humans.	considered to be carcinogenic.	_

Applies to Product :

Sensitization: No information available. No information available. Mutagenicity: Reproductive Toxicity: No information available. Teratogenicity: No information available. Neurological Effects: No information available.

Formaldehyde:

Eye - Rabbit Standard Draize test. : 750 ug - [severe](RTECS)

Skin:

Skin - Rabbit; Standard Draize test. : 2 mg/24H; severe. (RTECS)
Skin - Rabbit; LD50 : 270 mg/Kg; Details of toxic effects not reported other than lethal dose value.

(RTECS)

Inhalation - Rat LC50: 250 ppm/2H - [Behavioral - Tetany Behavioral - Coma Lungs, Thorax, or Respiration - Acute pulmonary edema] Inhalation:

Inhalation - Rat LC50: 203 mg/m3 [Peripheral Nerve and Sensation - Spastic paralysis with or without sensory change; Behavioral - Convulsions or effect on seizure threshold; Behavioral - Excitement] Inhalation - Mouse LC50: 454 mg/m3/4H - [Details of toxic effects not reported other than lethal dose value] (RTECS)

Inhalation - Mouse LC50: 505 mg/m3/2H - [Behavioral - Tetany Behavioral - Coma Lungs, Thorax, or Respiration - Acute pulmonary edema] (RTECS)

Ingestion:

Ingestion - Rat LD50: 100 mg/kg [Details of toxic effects not reported other than lethal dose value] Inhalation - Mouse LD50: 42 mg/kg [Behavioral - Somnolence (general depressed activity); Behavioral - Convulsions or effect on seizure threshold; Behavioral - Excitement] Inhalation - Mouse LD50: 385 mg/kg [Details of toxic effects not reported other than lethal dose

Inhalation - Mouse LD50: 500 mg/kg [Behavioral - Tremor; Liver - Other changes;

Kidney/Ureter/Bladder - Other changes] Inhalation - Rat LD50: 500 mg/kg [Behavioral - Tremor; Liver - Other changes; Kidney/Ureter/Bladder

Other changes](RTECS)

Carcinogenicity:

The International Agency for Research on Cancer (IARC) convened a working group of twenty-six scientists from ten countries in June 2004 to assess the carcinogenic hazard to humans of formaldehyde. The proceedings of that meeting have not yet been published. Based upon a press released issued by IARC, the Working Group concluded that there is sufficient evidence in humans that formaldehyde causes nasopharyngeal cancer, a rare tumor. The Working Group also concluded that there is "strong but not sufficient evidence for a causal association between leukemia and occupational exposure to formaldehyde". These findings where based on studies of workers in industries with long term exposures at levels greatly in excess of those typically associated with fiber glass insulation

Overall, the Working Group concluded that formal dehyde is carcinogenic to humans (Group 1), on the basis of sufficient evidence in humans and sufficient evidence in experimental animals-a higher classification than previous IARC evaluations.

Fiber Glass (Wool):

In June 2011, The National Toxicology Program (NTP) removed biosoluble glass wool fibers from its list of possible carcinogens used for home and building insulation. Chronic Effects:

In October 2001, the International Agency for Research on Cancer (IARC) classified fiber glass wool as Group 3,"not classifiable as to its carcinogenicity to humans". The 2001 decision was based on human studies and animal research that have not shown an association between inhalation exposure to dust

from fiber glass wool and the development of respiratory disease.

SECTION 12: ECOLOGICAL INFORMATION

Applies to Product:

Ecotoxicity: This material is not expected to cause harm to animals, plants or fish.

Environmental Stability: Not available.

Environmental Fate: No data available for this product.

Bioaccumulation: Not available. Biodegradation: Not available. Mobility In Environmental Media: Not available.

SECTION 13: DISPOSAL CONSIDERATIONS

Applies to Product:

Waste Disposal: Dispose of in accordance with Local, State, Federal and Provincial regulations.

RCRA Number: No EPA Waste Numbers are applicable for this product's components.

SECTION 14: TRANSPORT INFORMATION

Notes: This product is not regulated for shipping or transportation

SECTION 15: REGULATORY INFORMATION

Inventory Status

	Japan ENCS	EINECS Number	China	South Korea KECL	Australia AICS			
Formaldehyde		200-001-8						
Cured Binder				Listed: KECI Number - KE-35185	Listed: Assessed by NICNAS: No			
Fiber Glass (Wool)	Not listed	266-046-0	Listed	KE-17630	Listed			

	Canada DSL	TSCA Inventory		
	Ganada DOL	Status		
Cured Binder	Listed	Listed		
Fiber Glass (Wool)	Listed	Listed		

Applies to Product:

Canada WHMIS: Not controlled.

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): CA PROP 65:

WARNING! This product contains a chemical known to the State of California to cause cancer.

This product does not contain any chemicals which are subject to the reporting requirements of the Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III (40CFR, Part 372).

Section 311/312 Hazard

SARA:

Categories: Acute Health Hazard.: Chronic Health Hazard: Yes

Yes Risk of ignition.: Sudden Release of Pressure Hazard.: No Reactive Hazard: Nο

Clean Air Act: This product does not contain any Hazardous Air Pollutants (HAPs).

Fiber Glass (Wool):

EC Number: 266-046-0

State Right To Know

	RI	MN	IL	PA	MA
Fiber Glass (Wool)	Listed	Listed	Listed	Listed	Listed

	ŊĴ		
Fiber Glass (Wool)	No Data		

SECTION 16: ADDITIONAL INFORMATION

MSDS Creation Date: December 16, 1997 MSDS Revision Date: August 01, 2013

MSDS Revision Notes: Constituent, health hazard and formatting updates

MSDS Author:

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. Disclaimer:

Copyright@ 1996-2013 Actio Corporation. All Rights Reserved.

700 Series Board, Serie 700 de Fiberglas Product Code: 17020-NAM

Revision:: 08/01/2013