



SAFE USE INSTRUCTION SHEET

Creation Date 12-Apr-2005

Revision Date 29-Sep-2016

Version 3

0. GENERAL INFORMATION

This Safe Use Instruction Sheet is the document provided by Owens Corning to communicate safe handling and use instructions for manufactured articles neither regulated by OSHA Hazard Communication Standard, 29 CFR 1910.1200 nor by the Canada Hazardous Products Regulation SOR/2015-17 (WHMIS 2015)

1. IDENTIFICATION

Product Name	Duct Liner
Synonyms	QuietR® AcousticR® Duct Liner, Duraflex® II, QuietR® AcustiTEX™ Duct Liner, QuietR® Rotary Duct Liner, QuietR® Duct Liner Board
Product Code	OCIS00037
Recommended Use	No information available
Manufacturer Address	Owens Corning Insulating Systems, LLC One Owens Corning Parkway Toledo, Ohio 43659
Company Phone Number	1-800-GET-PINK or 1-800-438-7465
24 Hour Emergency Phone Number	Chemtrec 1-800-424-9300
Emergency Telephone	1-419-248-5330 (after 5 pm ET and weekends)
E-mail address	safetydatasheet@owenscorning.com
Company Website	http://owenscorning.com/

2. HAZARDS IDENTIFICATION

OSHA Regulatory Status	This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). This product is considered an article. 29 CFR 1910.1200(c) definition of an article is as follows: "Article" means a manufactured item other than a fluid or particle: (i) which is formed to a specific shape or design during manufacture; (ii) which has end use function(s) dependent in whole or in part upon its shape or design during end use; and (iii) which under normal conditions of use does not release more than very small quantities, e.g., minute or trace amounts of a hazardous chemical (as determined under paragraph (d) of this section), and does not pose a physical hazard or health risk to employees
WHMIS Regulatory Status	This product is considered an article per the Canadian Hazardous Products Regulation SOR/2015-17 Manufactured articles which meet the definition of the Canadian Hazardous Products Act (any article that is formed to a specific shape or design during manufacture, the intended use of which when in that form is dependent in whole or in part on its shape or design, and that, when being installed, if the intended use of the article requires it to be installed, and under normal conditions of use, will not release or otherwise cause an individual to be exposed to a hazardous product) are not regulated by the Canadian Hazardous Products Regulation SOR/2015-17
Other Hazards	May cause temporary skin and mucous membranes itching due to the mechanical abrasion

effect of fibers

3. COMPOSITION/INFORMATION ON INGREDIENTS

While fiberglass products may cause temporary skin and mucous membranes itching due to the mechanical abrasion effects of fibers, it does not meet the new classification definition of "irritant" contained in the OSHA HCS 29 CFR 1910.1000, Appendix A. OSHA now specifically defines an irritant as "a reversible inflammatory effect on living tissue by chemical action..." Owens Corning fiberglass is an inert material and does not interact chemically with the skin or mucous membranes

Fiberglass, Wool 90-99
Binder - PUF 1-10

4. FIRST AID MEASURES

Description of First Aid Measures

- | | |
|---------------------|---|
| Eye contact | <ul style="list-style-type: none">• Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes• DO NOT rub or scratch eyes• If eye irritation persists: Get medical advice/attention |
| Skin contact | <ul style="list-style-type: none">• Wash off immediately with soap and plenty of cold water• DO NOT use warm water because this will open up the pores of the skin, which will cause further penetration of the fibers• Use a wash cloth to help remove fibers• DO NOT rub or scratch affected area• Remove contaminated clothing and shoes• If skin irritation persists, call a physician• If fibers are seen penetrating from the skin, the fibers can be removed by applying and removing adhesive tape so that the fibers adhere to the tape and are pulled out of the skin• Never use compressed air to remove fibers from skin |
| Inhalation | <ul style="list-style-type: none">• Remove to fresh air• If symptoms persist, call a physician |
| Ingestion | <ul style="list-style-type: none">• Accidental ingestion of this material is unlikely• Rinse mouth with water and drink water to remove fibers from the throat• If this does occur watch person for several days to make sure intestinal blockage does not occur• If symptoms persist, call a physician |

5. FIRE-FIGHTING MEASURES

- | | |
|--|---|
| Suitable extinguishing media | <ul style="list-style-type: none">• Use extinguishing measures that are appropriate to local circumstances and the surrounding environment |
| Protective equipment and precautions for firefighters | <ul style="list-style-type: none">• As in any fire, wear self-contained breathing apparatus (positive-pressure), MSHA/NIOSH (approved or equivalent) and full protective gear |

6. ACCIDENTAL RELEASE MEASURES

- | | |
|--------------------------------|--|
| Personal precautions | <ul style="list-style-type: none">• Avoid contact with eyes and skin |
| Methods for cleaning up | <ul style="list-style-type: none">• Use an industrial vacuum cleaner with a high efficiency filter to clean up dust and fiber contamination• Avoid creating dust• Avoid dry sweeping• Pick up and transfer to properly labeled containers• Use personal protective equipment as required |

- Clean contaminated surface thoroughly

7. HANDLING AND STORAGE

- Storage Conditions**
- Keep product in packaging until use to minimize potential dust generation
 - Product should be kept dry and undercover

- Incompatible materials**
- None known based on information supplied

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH REL	Ontario TWA
Fiberglass wool 65997-17-3	TWA: 1 fiber/cm ³ respirable fibers: length >5 µm, aspect ratio ≥3:1, as determined by the membrane filter method at 400-450X magnification [4-mm objective], using phase-contrast illumination TWA: 5 mg/m ³ inhalable particulate matter	-	-	TWA: 1 fibre/cm ³ TWA: 5 mg/m ³

Engineering Controls Provide local exhaust and/or general ventilation to maintain exposure below regulatory and recommended limits
Dust collection system must be used in transferring operations, cutting or other dust generating processes, such as using power tools
Vacuum or wet clean-up methods should be used

Individual protection measures, such as personal protective equipment

- Eye/face protection**
- Wear safety glasses with side shields (or goggles)
- Skin and body protection**
- Wear protective gloves
 - Wear long-sleeved shirt and long pants
- Respiratory protection**
- When workers are facing concentrations above the exposure limit they must use appropriate certified respirators in accordance with their company's respiratory protection program, local regulations or 29 CFR 1910.134
 - A properly fitted NIOSH approved disposable N 95 type dust respirator or better is recommended

- General Hygiene Considerations**
- Wash hands before breaks and immediately after handling products
 - Remove and wash contaminated clothing before re-use

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State @20°C Solid
Appearance Fibrous
Odor Organic
Color Black
Water solubility Insoluble in water

10. STABILITY AND REACTIVITY

Possibility of Hazardous Reactions • None under normal processing

Hazardous Decomposition Products • None known based on information supplied

11. TOXICOLOGICAL INFORMATION

Product Information	Fiberglass wool may cause temporary skin and mucous membranes itching due to mechanical abrasion effect of fibers
IARC (International Agency for Research on Cancer)	In October 2001, the International Agency for Research on Cancer (IARC) classified fiber glass wool as Group 3, "not classifiable as to its carcinogenicity to humans". The 2001 decision was based on human studies and animal research that have not shown an association between inhalation exposure to dust from fiber glass wool and the development of respiratory disease
NTP (National Toxicology Program)	In June 2011, The National Toxicology Program (NTP) removed biosoluble glass wool fibers from its list of possible carcinogens used for home and building insulation

12. ECOLOGICAL INFORMATION

This product is not expected to be hazardous for the environment

13. DISPOSAL CONSIDERATIONS

Disposal should be in accordance with applicable regional, national and local laws and regulations

14. TRANSPORT INFORMATION

This material is not subject to regulation as a hazardous material for shipping

15. REGULATORY INFORMATION

International Inventories	This product is classified as an article. Articles are exempted from registration or listing under chemicals inventories like TSCA (USA), DSL/NDSL (CAN), REACH (EU), ENCS (JP), IECSC (CN), KECL (KR), PICCS (PH), AICS (AUS)
California Proposition 65	WARNING! This product contains a chemical known in the State of California to cause cancer

16. OTHER INFORMATION

Creation Date	12-Apr-2005
Revision Date	29-Sep-2016
Revision Note	SUIS Section Updated 1,

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safe Use Instruction Sheet